

Tigerloop®

Bio™

NEW!

A standard Tigerloop® with B100 compatibility!


Totally **Metallic** Housing



Technical Information

MAX. NOZZLE CAPACITY	20 GPH
MAX. RETURN OIL FLOW	30 GPH
TEMPERATURE RANGE	20° - 105° F
MAX. INLET PRESSURE	8 PSI
CONNECTIONS	1/4" - NPT (female)
FUEL	B100 BioHeat®, No. 1 & 2 OIL

Not for use with E-diesel or any fuel containing Ethanol (alcohol)

 No.	Description
S220-1	Tigerloop® Bio™ oil de-aerator for biofuels to B100

Tigerloop®

ULTRA-B™

NEW!

A standard Tigerloop® ULTRA™ with B100 compatibility!


Totally **Metallic** Housing



Technical Information

MAX. NOZZLE CAPACITY	20 GPH
MAX. RETURN OIL FLOW	30 GPH
TEMPERATURE RANGE	20° - 105° F
MAX. INLET PRESSURE	8 PSI
CONNECTIONS	1/4" - NPT (female)
REPLACEMENT ELEMENT	F100-10
ELEMENT MEDIA	10 Micron
ELEMENT CANISTER	EPOXY INSIDE
FUEL	B100 BioHeat®, No. 1 & 2 HEATING OIL

Not for use with E-diesel or any fuel containing Ethanol (alcohol)

 No.	Description
S220-9	Tigerloop® ULTRA™-B oil de-aerator & filter

exclusive importer

Westwood

Westwood Products Inc., South River, NJ 08882
1-800-442-1630

